

US011362564B2

(12) United States Patent Driker et al.

(54) TEMPERATURE COMPENSATED LINEAR ACTUATOR AND ENCODER

(71) Applicant: KappaSense Ltd., Misgav (IL)

(72) Inventors: Michael Driker, Ma'alot (IL); Bóris Kilunov, Karmiel (IL); Stanislav

Podlisker, Nahariya (IL)

(73) Assignee: Kappasense Ltd., Misgav (IL)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 1216 days.

(21) Appl. No.: 15/716,842

(22) Filed: Sep. 27, 2017

(65) Prior Publication Data

US 2018/0091017 A1 Mar. 29, 2018

(30) Foreign Application Priority Data

Sep. 29, 2016 (EP) 16191424

(51) Int. Cl. H02P 21/06 (2016.01) H02K 11/21 (2016.01) H02K 7/00 (2006.01) H02K 41/03 (2006.01) H02K 11/25 (2016.01) H02K 5/04 (2006.01)

(Continued)

(52) U.S. Cl.

 (10) Patent No.: US 11,362,564 B2

(45) Date of Patent:

Jun. 14, 2022

(58) Field of Classification Search CPC H02K 7/08; H02P 25/06; H02P 8/14

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

6,074,382 A * 6/2000 Asah A61B 18/203

606/10

6,167,634 B1 1/2001 Pahk et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 3040688 A2 7/2016 WO 03039810 A1 5/2003

OTHER PUBLICATIONS

European Search Report completed Apr. 3, 2017, pertaining to EP16191424 filed Sep. 29, 2016.

ABSTRACT

Primary Examiner — Muhammad S Islam
Assistant Examiner — Charles S Laughlin
(74) Attorney, Agent, or Firm — Dinsmore & Shohl LLP

(1.1) The mey, 11gens, or 1 time Distincte & C

A linear actuator includes a casing that contains a moveable shaft moved by a motor in response to a drive signal and coupled to an encoder that determines an actual instantaneous position of the shaft and forms part of a control loop that adjusts the drive signal so as to ensure accurate positioning of the shaft. A temperature sensor mounted on the shaft produces a temperature signal indicative of instantaneously measured temperature, and a temperature compensator responsive to the measured temperature for generating a negative or positive offset for correcting the drive signal so as to move the shaft to a positon that is corrected for instantaneous expansion or contraction of the shaft owing to departures of the shaft's actual temperature from a known baseline temperature.

14 Claims, 7 Drawing Sheets

